



IBM System Storage®

IBM Network Advisor v12.4.2 Release Notes

Copyright © 2015 Brocade Communications Systems, Incorporated.

Copyright © IBM Corporation 2015. All rights reserved.

Brocade, and Fabric OS are registered trademarks and the Brocade B-wing symbol, DCFM, DCX, and Fabric OS, and are trademarks of Brocade Communications Systems, Inc., in the United States and/or in other countries. Other brands, products, or service names mentioned are or may be trademarks or service marks of their respective owners.

IBM, the IBM logo, and [ibm.com](http://www.ibm.com) are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both. A complete and current list of other IBM trademarks is available on the Web at <http://www.ibm.com/legal/copytrade.shtml>

Notice: This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered or to be offered by Brocade or IBM. Brocade and IBM reserve the right to make changes to this document at any time, without notice, and assume no responsibility for its use. This informational document describes features that may not be currently available. Contact an IBM representative for information on feature and product availability.

The authors, Brocade Communications Systems, Inc., and IBM Corporation shall have no liability or responsibility to any person or entity with respect to any loss, cost, liability, or damages arising from the information contained in this book or the computer programs that accompany it.

Notice: The product described by this document may contain "open source" software covered by the GNU General Public License or other open source license agreements. To find-out which open source software is included in Brocade products, view the licensing terms applicable to the open source software, and obtain a copy of the programming source code, please visit <http://www.brocade.com/support/oscd>.

Export of technical data contained in this document may require an export license from the United States Government.

CONTENTS

Release overview	4
Software feature overview	4
SAN Management feature enhancements	4
Operating Systems supported	5
Browser support	6
Device platform and firmware requirements	8
Installing IBM Network Advisor	8
To install IBM Network Advisor on Windows (Server).....	8
To install IBM Network Advisor on Linux (Server).....	8
To launch the IBM Network Advisor client	9
Important SAN Notes	10
Display of Logical switches	12
SSL connections using certificates with MD5 signatures.....	12
Reset Ports operation in Logical Switches dialog	12
Additional important notes for SAN	13
Patch installer troubleshooting	15
Support Saves may take a long time with large databases	15
Installation on network mounted drives is not supported	15
Client disconnects	15
Performance statistics counters - calculation formulae	15
SMI Agent	17
Indications delivery depends on SAN size and SNMP registration.....	17
CIMOM heap size.....	17
Logging for CIMOM	17
Service Location Protocol (SLP) support	18
Documentation updates	20
Defects	21
Open Defects in IBM Network Advisor 12.4.2	21
Defects closed with code change in IBM Network Advisor 12.4.2	31

Release overview

IBM Network Advisor 12.4.2 is a software maintenance release based on IBM Network Advisor 12.4.1. All hardware platforms and features supported in IBM Network Advisor 12.4.1 are supported in 12.4.2. This release supports key FC SAN features including support for Fabric OS 7.4, IP Storage Management, and enhancements to Reporting, Usability, and REST API library.

IBM Network Advisor is a software management platform for SAN networks. It provides network administrators the ability to quickly access network topology, health and performance data required to troubleshoot and remediate network issues. IBM Network Advisor is licensed and deployed to manage SAN only networks.

The fixes included in this release are listed in the defect tables at the end of this document.

Software feature overview

SAN Management feature enhancements

IBM Network Advisor 12.4.2 supports the following SAN capabilities and enhancements:

- Platform support
 - FOS 7.4
- COMPASS
 - Custom configuration blocks and templates
 - Template configuration from existing switch config
 - Create/Edit/Delete user-defined switch groups
 - Link templates to fabrics or user-defined switch groups
 - Monitor configuration drifts on linked switches
 - Dashboard widget to monitor configuration drifts
- IP Storage
 - Display in property sheets
 - Dashboard support for monitoring Port Health
 - Storage port details in Network OS cluster reports
- IP Extension
 - Enhancements to Topology, FCIP Tunnel Config dialog
 - Support to configure FC & IP compression modes
 - Support for QoS distribution settings
 - Adaptive Rate Liming configuration
 - HA config support for existing circuits
- Web Client Enhancements
 - Real Time Graph widget support
 - Dashboard Playback support
 - Event page enhancements
 - REST API enhancements
- Dashboard Enhancements
 - Enhancements to Network Scope – Zones and Zone Alias
- MAPS Enhancements
 - Bottleneck detection indication
 - Support for new actions: FMS, Toggle, SDDQ etc.
 - Selective distribution of policies
 - Clear E-mail support
- Zoning Enhancements
 - Support for Peer, LSAN peer and Target Driven Peer Zones
- FICON
 - Enhancements to Configure Cascaded FICON Fabric dialog
 - FICON Merge Wizard enhancements

- Encryption & Compression configuration
- Fault Management Enhancements
 - New KPI widget in Dashboard
 - Master Log enhancements
 - Audit Log enhancements
- Other Enhancements
 - Flow Vision – Zone Alias support
 - Port Decommission enhancements
 - SAN42B-R Base Switch support
 - Fabric Watch deprecation for Fabric OS V7.4.0 and later
 - Embedded server JRE upgraded to version 1.7u80
 - Remote client JRE support for 1.8u51
 - Jserver upgrade to 3.10

IBM Network Advisor upgrades: IBM Network Advisor 12.2.0 and 12.3.3–12.3.4 running on the Linux and Windows operating systems can be upgraded to IBM Network Advisor 12.4.2.

Note 1: Enterprise and Professional Plus editions are not supported on 32-bit servers. To migrate Enterprise and Professional editions to a 64-bit server, refer to the “Pre-migration requirements when migrating from one server to another” section of the *IBM Network Advisor Installation and Migration Guide*.

Note 2: Direct migration from pre-12.2.0 releases to 12.4.2 is not supported. Refer to tables 9 and 10 in the *Installation and Migration Guide* for migration paths from DCFM and Network Advisor pre-12.2.0 releases.

Note 3: Refer to Table 11, “SMI Agent only migration paths,” in the *Installation and Migration Guide* for SMI Agent only migration paths.

Migration Impact:

New IBM model names for the IBM switches will not be shown automatically upon migration. To see these new names, edit the existing model name with that of the new name in the “oem-switch-model-mapping.properties” file located in the ‘conf’ folder of NA home location. Restart the server to make changes take effect.

Operating Systems supported

IBM Network Advisor 12.4.x is supported on the following operating systems.

Note: The minimum required system physical memory for running IBM Network Advisor 12.4.x (server plus one local client) for the different editions is as listed below:

- Pro-plus and Enterprise Editions (supported on 64-bit OS only):
 - Small SAN fabric network: 6 GB
 - Any combination that includes a small/medium/large SAN fabric network: 16 GB

Table 1 64-bit server / client operating system support

Operating System (architecture) / Installer	Versions
Windows	<ul style="list-style-type: none"> Windows 8 and 8.1 Enterprise
Windows Server	<ul style="list-style-type: none"> Windows Server 2008 R2 Datacenter, Standard, and Enterprise Windows Server 2012 and 2012 R2 Standard, Datacenter
Linux	<ul style="list-style-type: none"> Red Hat Enterprise Linux Adv6.4, 6.5, 6.6, 7.0 Oracle Enterprise Linux 6.4, 6.5, 7.0 SUSE Linux Enterprise Server 11.3, 12.0

Browser support

Recommended browser versions for Web client:

- Internet Explorer 11.0.9 update version RTM (Windows 8.1, Windows Server 2008 R2, Windows Server 2012 R2)
- Internet Explorer 10.0.9 update version RTM (Windows 2012)
- Firefox 37 and later (Windows/Linux)
- Chrome 41 and later (Windows)

Table 2 JRE support

IBM Network Advisor version	JRE version supported
12.0.2	JRE 1.7u17
12.0.3, 12.1.2, 12.1.3	JRE 1.7u25
12.0.4, 12.1.4, 12.1.5	JRE 1.7u45
12.1.6	JRE 1.7u45 and JRE 1.7u51 [Windows] JRE 1.7u67 [Linux]
12.3.2	JRE 1.7u67
12.3.3	JRE 1.7u71, 1.7u72
12.3.4	JRE 1.7u76, 1.8_u31
12.4.1	JRE 1.7u 79, 1.7u80, 1.8_u45
12.4.2	JRE1.7u79,1.7u80,1.8_u51

Note 1: Web Tools launched from IBM Network Advisor is also supported for the above combinations.

Note 2: (Applicable only to WebTools from FOS releases done before 2/13/2015.) Due to java signing certificate expiration, Web Tools launched from IBM Network Advisor will not work with JRE. An attempt to launch the Web Tools will be blocked and “Failed to validate certificate. The application will not be executed” message will display. To work around this issue, uninstall JRE 8, install JRE 7 updates 79/80 and set the security level to Medium.

For users with JRE 7 installation, an attempt to launch the Web Tools will be blocked and “Application Blocked by Security Settings” message will display. To work around this issue, JRE 7 users can simply reduce the security level from High to Medium and continue using JRE 7 update 79/80.

Note 3: Oracle enforces the latest JRE update to be used to web start the applications. The recommended versions for this release are listed in the JRE support table. Beyond the JRE expiration date, users will see the message “**Your Java version is out of date**” on an attempt to launch the web client.

You can either ignore the message “Your Java version is out of date” by selecting the “**later**” option and then proceeding with the web start client, or you can install the latest released JRE patch and then web start the client. The following warning will display and can be ignored: “The client system has java version <Latest Installed JRE> but the recommended java version is <as noted in the JRE support table>. Do you want to continue?”

Note 4: JRE 1.7.0 update 51 and later support begins with the following Fabric OS versions:

- Fabric OS v6.4.3f
 - Fabric OS v7.0.2e
 - Fabric OS v7.1.1c
 - Fabric OS v7.1.2
 - Fabric OS v7.2.1
 - Fabric OS v7.3.0
 - Fabric OS v7.4.0
- a. Apply the following workaround when launching WebTools using a browser or NetworkAdvisor Remote client for all Fabric OS versions earlier than the ones listed above:
- On Windows:
Go to C:\Program Files\Java\jre7\lib\security
 - On Linux:
Go to <jre install directory>/lib/security
 - Edit java.security file and change the value to 256 from 1024 for
jdk.certpath.disabledAlgorithms=MD2, RSA keySize < 1024
- Apply the following workaround on the Network Advisor server when launching Element Manager from the Network Advisor client for all Fabric OS versions earlier than the ones listed above:
- On Windows:
Go to <Network Advisor install directory>\jre64\lib\security
 - On Linux:
Go to <jre install directory>/lib/security
 - Edit java.security file and change the value to 256 from 1024 for
jdk.certpath.disabledAlgorithms=MD2, RSA keySize < 1024

Table 3 Supported scalability limits by Network Advisor editions

	Enterprise edition			Professional Plus edition
	Small	Medium	Large	
SAN switch ports	2000	5000	15000	2560
SAN switches and Access Gateways	40	100	400	40
SAN devices	5000	15000	40000	5000
SAN Fabrics	25	50	100	36
Managed Hosts	20	100	400	100
vCenters	1	5	10	5
VMs (includes powered down VMs)	1000	5000	10000	5000

Note: Virtual Fabrics are counted as fabrics when calculating the managed count limits.

Note: Supported network latency between Network Advisor server and client or server and devices is 100ms.

Device platform and firmware requirements

The following table lists the versions of Brocade software supported in this release. IBM and Brocade recommend using the latest software versions to get the greatest benefit from the network. IBM and equivalent Brocade hardware products are listed.

Operating System	IBM Switch/Director	Brocade Switch/Director
Switch (b-type and B-Model) firmware versions		
FOS 5.0.x, 5.1.x, 5.2.x, 5.3.x, 6.0.x, 6.1.x, 6.2.x, 6.3.x, 6.4.x, 7.0.x, 7.1.x, 7.2.x, 7.3.x, and 7.4.x	SAN24B-4 Express (2498-B24, -24E) SAN40B-4 (2498-B40, -40E) SAN80B-4 (2498-B80) SAN24B-5 (2498-F24, 249824G, 2498-X24) SAN48B-5 (2498-F48) SAN96B-5 (2498-F96, -N96) SAN04B-R (2005-R04) SAN06B-R (2498-R06) SAN 42B-R (2498-R42) IBM Converged Switch B32 (3758-B32, -L32) VA-40FC SAN256B (2109-M48) SAN384B (2499-192) SAN768B (2499-384) SAN384B-2 (2499-416) SAN768B-2 (2499-816)	Brocade 300 Brocade 5100 Brocade 5300 Brocade 6505 Brocade 6510 Brocade 6520 Brocade 7500E Brocade 7800 Brocade 7840 Brocade 8000 VA-40FC Brocade 48000 Brocade DCX-4S Brocade DCX Brocade DCX 8510-4 Brocade DCX 8510-8

Installing IBM Network Advisor

Refer to the *IBM System Storage Network Advisor Installation and Migration Guide* for complete installation instructions. The installation instructions below provide a brief overview for the following operating systems:

- Microsoft Windows
- Linux

The Network Advisor Server runs as multiple services on Windows and multiple processes on Linux; they start automatically after installation.

To install IBM Network Advisor on Windows (Server)

1. Download and extract the zip archive
2. Navigate to the **Windows** folder
3. Run *install.exe*
4. Follow the instructions to complete the installation.

To install IBM Network Advisor on Linux (Server)

1. Download and extract the *tar.gz* archive
2. Navigate to the **Linux** folder.

3. Run *Install.bin* from the **File Manager** window.
4. Follow the instructions to complete the installation.

To launch the IBM Network Advisor client

To launch the IBM Network Advisor client on the same local machine as the Network Advisor server, launch the client as follows:

Windows:

- Select: **Start > Programs > Network Advisor 12.4.x > Network Advisor 12.4.x**
- Launch the client from the desktop icon.
- Launch command prompt and go to the location "<Install location>/bin" and enter "**dcmclient**"

Linux:

- Launch the client from the desktop icon.
- Launch terminal and go to the location "<install location>/bin" and enter "**sh dcmclient**"

Web browser, Windows and Linux: Follow the steps below for launching the client from a web browser.

1. To launch the IBM Network Advisor client from a remote host, launch the client as follows:
Open a browser window and type the IBM Network Advisor server hostname or IP address in the **Address** field; for example:
<https://NetworkAdvisorServerhost1.companyname.com/>
<https://192.x.y.z/>
2. If, when the Network Advisor server was installed, a Network Advisor web server HTTPS port number was specified (instead of the default 443), you must specify the port number after the hostname or IP address. In the following examples, 8080 is the web server port number:
<https://NetworkAdvisorServerhost1.companyname.com:8080/>
<https://192.x.y.z:8080/>

Note 1

The web started remote client is supported with JRE versions listed in the JRE support section in this document. The supported JRE version needs to be installed on the remote client system prior to establishing a server connection.

Note 2

The remote client can be launched in the following ways:

- Enter the server IP in the browser. The page will redirect to web client login page. Select the "Desktop client" option. A page will display with two options to start the remote client:
 - Web start the client
 - Download the client bundle (64-bit OS only). (Supported for the same or cross-OS platforms.)
- Enter the server IP in the browser. The page will redirect to web client login page. Log in to the web client and then select the "Desktop Client" menu option for remote client launch

Note 3

Launching the element manager applications within the Network Advisor client is done using Java Web Start technology. This requires that the local system's web browser is able to run Java web start applications. This setting may have been turned off, due to recent Java zero-day vulnerabilities.

To turn on Java content in the browser, follow the steps below:

1. Launch the "Java Control Panel"
(refer to http://java.com/en/download/help/win_controlpanel.xml to locate the Java Control Panel application on Windows)
2. In the Java Control Panel, click the **Security** tab.
3. Select the **Enable Java content in the browser** check box. This will enable the Java plug-in for the browser.
4. Click **Apply**. When the Windows User Account Control (UAC) dialog appears, allow permissions to make the changes. Click **OK** in the Java Plug-in confirmation window.
5. Now launch Element Manager from the IBM Network Advisor client.

Important SAN Notes

1. For the Professional edition of IBM Network Advisor, the support for SAN fabric count increased from 1 to 2 fabrics and support for switch port count is reduced from 1000 to 300 switch ports.
2. If you see the following error message "Signature could not be validated" during firmware download or technical support data collection using SCP/SFTP, then it could be due to a mismatch in the signature key used in the ssh handshake between the switch and SCP/SFTP server. Use the following CLI command work around to address the issue:
 - For Fabric OS devices
sw0:FID128:admin> sshutil delknownhost

IP Address/Hostname to be deleted: <IP Address of SSH server to be deleted>If this work-around does not work, go to Server > Options > Software Configuration > FTP/SFTP/SCP, and deselect the SCP/SFTP option.
3. If you see the following error message "Remote Host: Could not connect to remote host." During technical support data collection (Fabric OS and Network OS devices only) using SCP/SFTP, then it could be due to a mismatch in the signature key used in the ssh handshake between the switch and SCP/SFTP server. Try the following cli command work-around to address the issue:
 - For Fabric OS devices
sw0:FID128:admin> sshutil delknownhost

IP Address/Hostname to be deleted: <IP Address of SSH server to be deleted>If this does not work, go to Server > Options > Software Configuration > FTP/SFTP/SCP, and uncheck the SCP/SFTP option
4. Firmware Download fails if built-in SCP is used as preferred protocol. The workaround is to use the FTP option in IBM Network Advisor.
5. Trying to move a large number of ports (200+) between logical switches with the 'Reset to Default' option selected, results in operation time-out.
6. During installation, if Network Advisor database initialization fails on Windows Operating System, verify access to the drive where the installation is located. If the user "Administrator"

alone has access to the drive, then required permissions should also be provided to “Authenticated Users”. Then continue with the installation.

7. The FCIP links will not be shown in the topology for tunnels with degraded circuits.
8. IP Ping, IP Route, and Trace route is not supported for SAN42B-R.
9. User cannot edit the tunnel configured without HA circuit for SAN42B-R.
10. IBM Network Advisor uses SNMPv3 by default to discover SAN products. If required, you can select the ‘Manual’ option in the **Discovery** dialog and choose SNMPv1 for discovery, as in case of AG discovery which requires use of SNMPv1 by default
11. A delay of 5 to 7 minutes is seen when Web Tools is launched on a system (through Network Advisor or directly in a web browser) where internet access is not available and the network does not return a ‘destination unreachable’ message. This issue occurs as Java tries to validate the SSL certificates with external CAs. This problem can be avoided on such systems by modifying the below Java properties:

On Windows: C:\Users\AppData\LocalLow\Sun\Java\Deployment\deployment.properties

On Linux: home/< logged in user name>/.java/deployment/deployment.properties

In the ‘deployment.properties’ file, edit the parameters below and set them to ‘false’.

If these parameters are not present, add them and then save the file. Then re-launch Web Tools.

deployment.security.validation.ocsp = false
deployment.security.validation.crl = false

12. Real time graph will not display proper data for FCIP tunnels when the polling interval is 10 sec. User need to keep 20 sec polling interval in graph to see the correct data for SAN42B-R.
13. Emulex: HTTPS discovery for ESXi host will work only with certificate import
14. If IBM Network Advisor is installed on Linux Operating System, the Fabric OS Element Manager and HCM cannot be launched if the client is launched using dcmclient script available in the Network Advisor installation folder. The Launch in Context (LIC) dialogs from the SMIA configuration tool (launched from Server Management Console) also cannot be launched (e.g. Discovery Dialog, Options Dialog etc.). To use the above features on Linux machines, launch IBM Network Advisor client from a browser (after installing the supported JRE version), pointing to the Network Advisor server installed on that machine.

Workaround

Complete the following two steps to work around this issue.

Step 1) Add following line in the <<User Home>/.java/deployment/deployment.properties file.

deployment.expiration.check.enabled=false

For example, if the user is root then the absolute path of this file would be as follows:

/root/.java/deployment/deployment.properties.

Step 2) Launch the Java Control Panel using the command below and then click **OK**.

<Network Advisor Home>\jre\bin\jcontrol

15. Secure Syslog is not supported from Network Advisor. Configuration of Quiet time from **Maps Configure** dialog is not recommended from IBM Network Advisor.

17. SAN Configuration Purge Backup is being enabled automatically when “Enable Scheduled Backup” is set and remains enabled after disabling the scheduled backup.
18. Session timeouts observed in Reports page of the Web Client after five minutes. Browser refresh is required to proceed.
19. User should not perform any write operations on FCIP tunnels which have circuits with different IDs.
20. When CIMOM server is bound to host name, SLP service fails to get registered. Workaround: To overcome this issue user can bind the CIMOM server to IP Address instead of host name.
21. Firmware upgrade will happen serially for SAN42B-R switches with HA configured tunnels between them. For parallel download on SAN42B-R switches use CLI
22. FCIP circuit trace route verification fails when attempted from Network Advisor

Display of Logical switches

If you create Logical switches through the **Logical Switch** dialog box, the logical switch displays under **Undiscovered Logical Switch** in the **Existing Logical Switches** panel. You have to rediscover the newly created logical switch fabric by opening the **Discovery** dialog and add the IP address of the chassis using the **Add** dialog.

SSL connections using certificates with MD5 signatures

After upgrading to IBM Network Advisor 12.x from 11.x, SSL-based product communication will fail if the devices have ‘weak’ authentication certificates. The user will see “Fabric Discovery failed because SSL certificate of the seed switch uses a weak algorithm. Install SSL Certificate with strong authentication algorithm on the switch and try again” for devices with weak certificates. Devices discovered prior to migration will not be manageable in IBM Network Advisor after migration. Java 1.7 used by IBM Network Advisor 12.x disables the use of certificates with ‘weak’ authentication. The certificates on such devices need to be updated to be compliant with JRE v1.7. Please refer to the ‘Secure Sockets Layer protocol’ section of FOS Admin guide for details on updating certificates

The recommended solution is to replace the certificate on the network device with a certificate using the more secure SHA signature. If that is not practical, the Network Advisor server configuration can be changed to accept MD5 signatures. Note that accepting MD5 signatures may result in warnings from network security scanning tools.

To accept MD5 signatures, edit the following text file:

On 64-bit Windows or Linux: <install-dir>/jre64/lib/security/java.security

Remove “MD5” from the following line near the end of the file:

```
jdk.tls.disabledAlgorithms=MD5, DES, 3DES, RC2
```

The modified line should appear as:

```
jdk.tls.disabledAlgorithms=DES, 3DES, RC2
```

The change will take effect the next time the Network Advisor server is restarted.

Reset Ports operation in Logical Switches dialog

Note 1:

Reset ports to default operation is applicable only when the ports are moved from one logical

switch to another logical switch through the right arrow button i.e., from (Chassis ports Tree/Tree Table) LHS to (Logical Switches Device Tree) RHS device tree.

It is not applicable when:

- Ports from a Logical Switch are moved to default Logical Switch through Left Arrow button, i.e., from (Logical Switches Device Tree) RHS to (Chassis ports Tree/Tree Table) LHS.
- When a Logical Switch is deleted - its ports will not be reset to default before moving to Default Logical Switch before its deletion

Ports which are moved to the default logical switch can be reset to default, if they are moved from Chassis ports Tree/Tree Table LHS to Logical Switches Device Tree RHS device tree.

Note 2:

Reset ports to default operation will not clear FCIP configurations in the following scenarios:

- In IBM SAN06B-R switches and FX8-24 blades, GE ports cannot be reset to default unless their corresponding VE ports are cleared of their FCIP configurations.
- Switch reset to default operation on IBM SAN42B-R switches may fail due to GE port sharing or if the associated VE port exists in another LS.

Additional important notes for SAN

1. 64 bit OS is required to run Network Advisor Professional-Plus and Enterprise Editions.
2. User role privileges related to SAN and IP features are prefixed with 'SAN -' and 'IP -' strings. After migration from an older version, new privilege names will be displayed in the **Role Management** dialog with these prefixes.
3. IBM Network Advisor server startup and restart can take up to 10+ minutes to complete.
4. To avoid excessive telnet/ssh login messages in the IBM Network Advisor master log and event report, and the device CLI console, disable lazy polling by deselecting the "Enable lazy polling" checkbox in **IP Discovery Global Settings > Preferences Dialog**.
5. Starting with 12.0, the number of client connections supported has increased to 25. Refer to the *Installation and Migration Guide* for details. In addition to those details, the following database memory setting is required:
 - The PostgreSQL's parameter "shared_buffers" memory allocation should be increased to 1024 MB. To change this setting, edit the <installation_directory>\data\databases\postgresql.conf file.
Change the line: shared_buffers = 256 MB
To: shared_buffers = 1024 MB
 - The server needs to be restarted.
6. In Linux 64 bit machines, connecting to the database through Open Office using ODBC will not work. The solution is to connect from Windows ODBC Client to the 64 bit Linux machine where IBM Network Advisor is running to view the Database tables.
7. If you are using the ODBC connection from a remote host to the database, after migrating to 12.0.x, you will no longer be able to connect from the remote host. If you want to connect from the remote host, refer to the "Configuring remote client access to the database" section in the *Installation and Migration Guide*.
8. Technical Support data collection for discovered Products fails through an external Linux FTP server on a Windows installation of Network Advisor. To successfully collect support save data for NOS and FOS devices, the following configuration needs to be done in the VSFTPD FTP server before triggering the support save by setting external VSFTPD FTP Linux server (other than NA FTP server):

/etc/vsftpd.conf file and set "chroot_local_user=YES"

9. The client only application can be installed on a machine other than the server (without using a web browser) by creating a client bundle on the server, then copying and installing that client on another machine. Refer to the 'Client only installation' section of the *Installation and Migration Guide* for details.
10. "Server is not available" message will be displayed in the **login** dialog when user changes the default server port [24600] and tries to launch a remote client from client bundle. It is recommended to use the default server port.
11. Intermittently HTTP 500 error message is displayed when launching the Web Client. Server restart will fix the issue.
12. Error code 10003 reads "Common DCFM error". Instead it should read "10003: [...] Another transaction in progress".
13. User needs to run the "sanperformancestatenable" script from NA home utilities folder to enable/disable performance statistics collection for SMIA only package installation. Following are the steps to execute the script.
 - Windows: Open cmd prompt and move to <BNA_HOME>\utilities and run sanperformancestatenable.bat dbusername dbpassword enable|disable
 - Linux: Open terminal and move to <BNA_HOME>\utilities and run sanperformancestatenable dbusername dbpassword enable|disable
14. User needs to use a different name (non-default) for the widget when attempting to add "Top Product Response Time" widget to avoid this error "Monitor could not be added. Duplicate monitor name".
15. Intermittently the Port Traffic/SFP/Error Time Series Report generation may fail when the port count is greater than 50 and the Time Scope is greater than 3 days.
16. REST API does not provide FCIP circuit measures for the GigE port.
17. "CLI through server" for FC/LC mode cluster and CLI Template based deployments for LC mode cluster will not function when product communication is set to "SSH Only".
18. IBM Network Advisor is now enforcing minimum disk space requirements during migration. When the disk space requirements are not met, IBM Network Advisor displays an error message prompting the user to use the script to delete performance data and retry migration.
19. The following step from the "Migration Data" section of the *Installation and Migration Guide* is no longer applicable and can be ignored during the migration: "To migrate historical performance data, select the SAN and IP check boxes, if necessary."
20. SNMP Trap auto-registration does not happen for a discovered VCS which is configured with 'Read Only' community string alone. Registration can be done manually post discovery through **Product Trap Recipients** dialog.
21. When IBM Network Advisor is managing more than 1500 IP products, you may experience some performance degradations such as delays while launching some dialogs.
22. Due to Microsoft Windows operating system restriction which does not allow services logged in as Local System user to interact with the desktop, the GUI application cannot be launched using "Launch a Script" option of **Add Event Action**.

Refer the following link for more information:
<http://msdn.microsoft.com/en-us/library/windows/desktop/ms683502%28v=vs.85%29.aspx>
23. LDAP users have to provide usernames with case sensitivity, as defined in LDAP server, to successfully login into Network Advisor client.
24. During migration, if insufficient space is detected, then a warning message will be displayed with an option to rollback. If user chooses "No", then migration will be aborted. As a result, the source version services will remain uninstalled. Please refer to the *Installation and Migration Guide* for instructions to install the source version services manually.

25. The firewall ports listed in the Installation and Migration guide need to be open bidirectionally for all the bi-directional protocols.
26. If the source Network Advisor has more products discovered, then it is recommended to stop all the services manually in the Network Advisor Server Management Console of the older version before initiating migration with the Configuration Wizard.
27. Reports: It is recommended to run no more than 50 schedules at the same time to avoid performance issues.
28. Service start up failure can be seen in Windows 2008 R2 OS and the recommendation is to apply this hot fix from <http://support.microsoft.com/kb/257779>

Patch installer troubleshooting

Patch installer may not launch if UAC is enabled on a Windows 7/8/2008/2008 R2/2012 editions. You must first disable the UAC using the procedure provided in the Appendix G: **Troubleshooting** section of the *User Manual*, and then launch the patch installer.

Support Saves may take a long time with large databases

As databases grow larger from Event, sFlow, and Performance Collector data, the Support Save operation may take a long time to run. Larger databases will promote longer Support Save operations. Make sure you have a minimum of 20GB disk space for Support Save and Backup operations.

Installation on network mounted drives is not supported

Installation onto a Windows network mounted drive is not supported but installation is allowed and the DB fails to start.

Client disconnects

Under heavy server load or degraded network links, there is a potential for the IBM Network Advisor client to get disconnected from the server. Work around is to restart the client.

Performance statistics counters - calculation formulae

For calculating the statistics for FC, GE, FCIP and TE port we use SNMP to query the respective OIDs, mentioned below in the table.

For calculating the HBA and CNA statistics, we use the APIs provided by HCM. And for EE monitors we use HTTP to get the TX, RX and CRC error values.

Polling interval for historical graph is 5 min and for real-time, it changes based on the granularity value selected in the Real Time graph dialog.

Counter Name	Type	Protocol used	Source value	Formula
TX	FC	SNMP	.1.3.6.1.3.94.4.5.1.6	$TX = (\text{Delta value}^1 / (1000 * 1000)) / (\text{Polling interval}^2)$
RX	FC	SNMP	.1.3.6.1.3.94.4.5.1.7	$RX = (\text{Delta value}^1 / (1000 * 1000)) / (\text{Polling interval}^2)$
TX	GE	SNMP	.1.3.6.1.2.1.31.1.1.1.10	$TX = (\text{Delta value}^1 / (1000 * 1000)) / (\text{Polling interval}^2)$
RX	GE	SNMP	.1.3.6.1.2.1.31.1.1.1.6	$RX = (\text{Delta value}^1 / (1000 * 1000)) / (\text{Polling interval}^2)$

TX	FCIP	SNMP	.1.3.6.1.2.1.31.1.1.1.10	$TX = (\text{Delta value}^1 / (1000 * 1000)) / (\text{Polling interval}^2)$
RX	FCIP	SNMP	.1.3.6.1.2.1.31.1.1.1.6	$RX = (\text{Delta value}^1 / (1000 * 1000)) / (\text{Polling interval}^2)$
Uncompressed Tx/Rx MB/sec	FCIP	SNMP	.1.3.6.1.4.1.1588.4.1.1.6	$(\text{Delta value}^1 / (1000 * 1000)) / (\text{Polling interval}^2)$
TX	EE Monitors	HTTP	PortRX (variable from the return html file)	$TX = (\text{Delta value}^1 / (1000 * 1000)) / (\text{Polling interval}^2)$
RX	EE Monitors	HTTP	PortTX (variable from the return html file)	$RX = (\text{Delta value}^1 / (1000 * 1000)) / (\text{Polling interval}^2)$
TX	HBA, CNA	HCM API	NA	$TX = (\text{Delta value}^1 / (1000 * 1000)) / (\text{Polling interval}^2)$
RX	HBA, CNA	HCM API	NA	$RX = (\text{Delta value}^1 / (1000 * 1000)) / (\text{Polling interval}^2)$
TX	TE	SNMP	.1.3.6.1.2.1.31.1.1.1.10	$TX = (\text{Delta value}^1 / (1000 * 1000)) / (\text{Polling interval}^2)$
RX	TE	SNMP	.1.3.6.1.2.1.31.1.1.1.6	$RX = (\text{Delta value}^1 / (1000 * 1000)) / (\text{Polling interval}^2)$
TX% / RX%	FC	NA	TX = .1.3.6.1.3.94.4.5.1.6 RX = .1.3.6.1.3.94.4.5.1.7	TX% or RX% for FC = $((\text{delta value1 of TX or RX}) / ((\text{Bytes transmitted} * \text{port speed}) * (\text{polling interval2})) * 100$ where Bytes transmitted for 1G,2G,4G,8G, and 16G port speed is 106250000 and Bytes transmitted for 10G port speed is 127500000. If utilization is less than 1, the value is 0.0.
TX% / RX%	GE	SNMP	TX = .1.3.6.1.2.1.31.1.1.1.10 RX = .1.3.6.1.2.1.31.1.1.1.6	TX% or RX% for FC = $((\text{delta value1 of TX or RX}) / ((125000000 * \text{port speed}) * (\text{polling interval2}))) * 100$. If utilization is less than 1, the value is 0.0.
TX% / RX%	FCIP	SNMP	TX = .1.3.6.1.2.1.31.1.1.1.10 RX = .1.3.6.1.2.1.31.1.1.1.6	TX% or RX% for FCIP = $((\text{delta value1 of TX or RX}) / (\text{maximum bytes transmitted}) * (\text{polling interval2}))) * 100$, where maximum bytes transmitted = tunnel speed
TX% / RX% (Pre 6.4.1 Edison release)	TE	SNMP	TX = .1.3.6.1.2.1.31.1.1.1.10 RX = .1.3.6.1.2.1.31.1.1.1.6	TX% or RX% for TE = $((\text{delta value1 of TX or RX}) / ((125000000 * 10) * (\text{polling interval2}))) * 100$. If utilization is less than 1, the value is 0.0.
Cumulative Compression Ratio	FCIP		.1.3.6.1.4.1.1588.4.1.1.4	Compression Ratio = current value/ 1000 Since for compression ratio we will take the current compression ratio value
Receive EOF	TE		.1.3.6.1.2.1.16.1.1.1.5	Receive EOF = $\text{Delta value}^1 / (1000 * 1000)$
Other Counters				Other counters = Delta value^1
Current Compression Ratio	FCIP	NA	NA	$(\text{ifHCInOctets} + \text{ifHCOctets}) / \text{fcipExtendedLinkCompressedBytes}$

- 1) Delta value¹: is the difference of value retrieved between the two consecutive polling cycles.
- 2) Polling interval²: duration between the two polling cycle in seconds

SMI Agent

1. For IBM Network Advisor that has more than 30K instances, the CIMOM takes more memory to generate CIM instances
2. If the user performs Enumerate Instances and the total size is more than 2 MB for all managed fabrics, it may result in out of memory issue. In this case, the user has to increase the CIMOM heap size to fetch zone database size of 2 MB.
Note: For 1.6 MB of zone database (144600 zone members), with 9 GB of heap size the Brocade_zonemembershipsettingdata instances are retrieved.

Indications delivery depends on SAN size and SNMP registration

The time to deliver the indication will vary based on Network Advisor SAN size selected during installation. If a large SAN size is selected, indication delivery time will be longer.

Provider classes may take more time to update the fabric changes if the switches managed in IBM Network Advisor are not SNMP registered. As this would cause a delay in indication delivery, all the switches managed in IBM Network Advisor should be SNMP registered

CIMOM heap size

The CIMOM heap size has been increase for small, medium, and large SAN network sizes:

Old heap sizes:

small

platform.64.cimom.conf.set.MAX_HEAP_SIZE = 1024m

medium

platform.64.cimom.conf.set.MAX_HEAP_SIZE = 1536m

large

platform.64.cimom.conf.set.MAX_HEAP_SIZE = 2048m

Current heap sizes:

small

platform.64.cimom.conf.set.MAX_HEAP_SIZE = 1536m

medium

platform.64.cimom.conf.set.MAX_HEAP_SIZE = 2048m

large

platform.64.cimom.conf.set.MAX_HEAP_SIZE = 3072m

Logging for CIMOM

The default logging level is "INFO" in integrated Agent. To change the logging level to DEBUG, update the "com.brocade" category value in cimom-log4j.xml file present in the <Installation Dir>\conf folder.

The log file size and number of log files also can be changed by modifying the file rolling appender parameters in this cimom-log4j.xml file.

Logging Level, File size and Number of Log files can be changed by modifying the following fields: "Log Level", "File Size" and "Number of Files" from the **Configuration Tool** through the **CIMOM** tab.

Service Location Protocol (SLP) support

The Management application SMI Agent uses Service Location Protocol (SLP) to allow applications to discover the existence, location, and configuration of WBEM services in enterprise networks.

You do not need a WBEM client to use SLP discovery to find a WBEM server; that is, SLP discovery might already know about the location and capabilities of the WBEM server to which it wants to send its requests. In such environments, you do not need to start the SLP component of the Management application SMI Agent.

However, in a dynamically changing enterprise network environment, many WBEM clients might choose to use SLP discovery to find the location and capabilities of other WBEM servers. In such environments, start the SLP component of the Management application SMI Agent to allow advertisement of its existence, location, and capabilities.

SLP installation is optional and you can configure it during Management application configuration. Once installed, SLP starts whenever the Management application SMI Agent starts.

Management SMI Agent SLP application support includes the following components:

- `slpd` script starts the `slpd` platform
- `slpd` program acts as a Service Agent (SA). A different `slpd` binary executable file exists for UNIX and Windows systems.
- `slptool` script starts the `slptool` platform-specific program
- `slptool` program can be used to verify whether SLP is operating properly or not. A different `slptool` exists for UNIX and Windows.

By default, the Management application SMI Agent is configured to advertise itself as a Service Agent (SA). The advertised SLP template shows its location (IP address) and the WBEM Services it supports. The default advertised WBEM services show the Management application SMI Agent:

- accepts WBEM requests over HTTP without SSL on TCP port 5988
- accepts WBEM requests over HTTPS using SSL on TCP port 5989

slptool commands

Use the following `slptool` commands to verify whether the SLP is operating properly.

- `slptool findsrvs service:service-agent`
Use this command to verify that the Management application SMI Agent SLP service is properly running as a Service Agent (SA).

Example output: `service:service-agent://127.0.0.1,65535`

- `slptool findsrvs service:wbem`
Use this command to verify that the Management application SMI Agent SLP service is properly advertising its WBEM services.

Example outputs:

```
service:wbem:https://10.0.1.3:5989,65535
```

```
service:wbem:http://10.0.1.3:5988,65535
```

This output shows the functionalities of Management application SMI Agent:

- accepts WBEM requests over HTTP using SSL on TCP port 5989
- accepts WBEM requests over HTTP without SSL on TCP port 5988
- `slptool findattrs service:wbem:http://IP_Address:Port`
 - Use this command to verify that Management application SMI Agent SLP service is properly advertising its WBEM SLP template over the HTTP protocol.
 - Example input: `slptool findattrs service:wbem:http://10.0.1.2:5988`
 - Note: Where `IP_Address:Port` is the IP address and port number that display when you use the `slptool findsrvs service:wbem` command.

- `slptool findattrs service:wbem:https://IP_Address:Port`
 - Use this command to verify that the Management application SMI Agent SLP service is properly advertising its WBEM SLP template over the HTTPS protocol.
 - Example input: `slptool findattrs service:wbem:https://10.0.1.2:5989`
 - Note: Where IP_Address:Port is the IP address and port number that display when you use the `slptool findsrvs service:wbem` command.

SLP on UNIX systems

This section describes how to verify the SLP daemon on UNIX systems.

SLP file locations on UNIX systems:

- SLP log—Management_Application/cimom /cfg/slp.log
- SLP daemon—Management_Application/cimom /cfg/slp.conf
- The SLP daemon can be reconfigured by modifying, SLP register—Management_Application/cimom /cfg/slp.reg

You can statically register an application that does not dynamically register with SLP using SLPAPIs by modifying this file. For more information about these files, read the comments contained in them, or refer to <http://www.openslp.org/doc/html/UsersGuide/index.html>

Verifying SLP service installation and operation on UNIX systems:

1. Open a command window.
2. Type `% su root` and press **Enter** to become the root user.
3. Type `# Management_Application/cimom/bin/slptool findsrvs service:service-agent` and press **Enter** to verify the SLP service is running as a Service Agent (SA).
4. Type `# < Management_Application >/cimom/bin/slptool findsrvs service:wbem` and press **Enter** to verify the SLP service is advertising its WBEM services.
5. Choose one of the following options to verify the SLP service is advertising the WBEM SLP template over its configured client protocol adapters.
 - Type `# Management_Application/cimom /bin/slptool findattrs service:wbem:http://IP_Address:Port` and press **Enter**.
 - Type `# Management_Application/cimom /bin/slptool findattrs service:wbem:https://IP_Address:Port` and press **Enter**.

Note: Where IP_Address:Port is the IP address and port number that display when you use the `slptool findsrvs service:wbem` command.

SLP on Windows systems

This section describes how to verify the SLP daemon on Windows systems.

SLP file locations:

- SLP log—Management_Application\cimom \cfg\slp.log
- SLP daemon—Management_Application\cimom\cfg\slp.conf
The SLP daemon can be reconfigured by modifying this file.
- SLP register—Management_Application\cimom\cfg\slp.reg
statically register an application that does not dynamically register with SLP using SLPAPIs by modifying this file. For more information about these files, read the comments contained in them, or refer to <http://www.openslp.org/doc/html/UsersGuide/index.html>

Verifying SLP service installation and operation on Windows systems:

1. Launch the **Server Management Console** from the **Start** menu.

2. Click **Start** to start the SLP service.
3. Open a command window.
4. Type `cd c:\Management_Application\cimom \bin` and press **Enter** to change to the directory where `slpd.bat` is located.
5. Type `> slptool findsrvs service:service-agent` and press **Enter** to verify the SLP service is running as a Service Agent.
6. Type `> slptool findsrvs service:wbem` and press **Enter** to verify the SLP service is advertising its WBEM services.
7. Choose one of the following options to verify the SLP service is advertising the WBEM SLP template over its configured client protocol adapters.
 - Type `> slptool findattrs service:wbem:http://IP_Address:Port` and press **Enter**.
 - Type `> slptool findattrs service:wbem:https://IP_Address:Port` and press **Enter**.

Note: Where `IP_Address:Port` is the IP address and port number that display when you use the `slptool findsrvs service:wbem` command.

Documentation updates

The most recent IBM Network Advisor 12.4.x documentation manuals are available on the IBM Support Portal site: www.ibm.com/supportportal. In the IBM Support Portal, select or enter the product name, and then select **Product documentation** under the **Product support content** heading. Navigate to the desired publications in the displayed results.

In the IBM Network Advisor SAN Manual, the capabilities and licensing requirements for the 16 Gbps FCIP router platform are not listed under the “Fiber channel over IP” chapter. That information is provided below and will be added in subsequent versions of IBM Network Advisor documentation.

Licensing:

The 16 Gbps FCIP router platform requires these FCIP licenses:

- WAN rate upgrade license 1
- WAN rate upgrade license 2
- Advanced Extension (FTR_AE)

Capabilities:

The 16 Gbps FCIP router platform has the capabilities of HA WAN Connectivity, FCIP trunking, Adaptive Rate Limiting, 10 GbE ports, 40 GbE ports, IP Extension Support, FC ports up to 16 Gbps, Compression, Open Systems Tape Pipelining (OSTP), FICON extension, IPSec for tunnel traffic, Diffserv priorities, VLAN tagging, IPv6 addresses for FCIP Tunnels, Support for jumbo frames.

Defects

Open Defects in IBM Network Advisor 12.4.2

This section lists the open defects with Critical, High, and Medium technical severity as of Aug 25, 2015 in IBM Network Advisor 12.4.2.

Defect ID: DEFECT000546803	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.0	Technology Area: Discovery
Symptom: The connections from an AG to the end device are not shown in certain cases.	
Condition: This occurs when the both the switch and AG are managed in Network Advisor and connection is shown from the switch to the end device instead of the AG to which it is connected.	

Defect ID: DEFECT000557247	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.3.4	Technology Area: Dashboard
Symptom: User will be able to see all members data/cluster information in PM product widgets.	
Condition: This issue occurs when user creates a Port scope with interfaces belonging to few members instead of the entire cluster.	

Defect ID: DEFECT000557388	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.1	Technology Area: Fabric Vision (SAN)
Symptom: User will see the warning message as the first message though there are other alarming errors in the flow definition which needs user interaction.	
Condition: In Add flow dialog, creating a flow on a Slave trunk E-port	

Defect ID: DEFECT000559296	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Device Management
Reported In Release: Network Advisor 12.4.1	Technology Area: Storage port mapping (SAN)
Symptom: User is able to create network scopes with end-devices (moving the WWPN and not the switch port itself). Such scopes are not effective and the dashboard doesn't show valid data.	
Condition: User must move only the end device attached to the switch port.	
Workaround: Move the switch port to which the end device is attached instead of or along with the end device.	
Recovery: Move the switch port to which the end device is attached instead of or along with the end device.	

Defect ID: DEFECT000559680	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Fault Management
Reported In Release: Network Advisor 12.4.1	Technology Area: Events & Logs
Symptom: Server Log size increases abnormally	
Condition: any NOS switch is discovered in Network Advisor.	

Defect ID: DEFECT000560741	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Fabric Vision (SAN)
Symptom: When user tries to assign FABRIC port under ALL_NAS_PORT & ALL_iSCSI_PORTS, the operation is successful instead of restricting the assignment	
Condition: When user tries to assign FABRIC port under ALL_NAS_PORT & ALL_iSCSI_PORTS	

Defect ID: DEFECT000560776	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Fabric Vision (SAN)
Symptom: MAPS port group name is not displayed in the ingress port of Flow definition / Sub flows in Flow Monitor dialog	
Condition: sys_analytics_vtap flow is updated with maps port group name that is available	

Defect ID: DEFECT000560777	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: View Management / Topology
Symptom: AF ports are displaying with missing icon in the Product tree and Topology	
Condition: Discover the AMP switch which has AF-Port connections and upgrade firmware.	

Defect ID: DEFECT000561227	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Dashboards
Symptom: Unwanted Scaling is set for Latency and Performance measures in the graph of Initiator Target and Initiator Target LUN flow widgets.	
Condition: Changing the measure type in table of IT/ITL flow widgets.	

Defect ID: DEFECT000561230	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Policy Monitor
Symptom: Remote SFP metrics test will not be performed on AE ports	
Condition: If the fabric contains at least one AMP device	

Defect ID: DEFECT000561489	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Fabric Vision (SAN)
Reported In Release: Network Advisor 12.4.2	Technology Area: Policy Monitor
Symptom: Able to edit sys_analytics_vtap flow	
Condition: Editing the sys_analytics_vtap flow for switch which is not connected to the AMP	

Defect ID: DEFECT000561607	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Monitoring)
Reported In Release: Network Advisor 12.4.2	Technology Area: Dashboards
Symptom: Negative values are shown in the IT/ITL flow widgets of Analytics Monitoring dashboard.	
Condition: Changing the measure values in IT/ITL flow widgets of Analytics Monitoring dashboard.	

Defect ID: DEFECT000561613	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Dashboards
Symptom: Predefined measures are not selected by default and graph is not plotted for 'Top Initiator Target Flow Latency' or 'Top Initiator Target LUN Flow Latency' dashboard	
Condition: This occurs when 'Other Command Latency' measure is selected from the 'Top 10' combo box of 'Top Initiator Target Flow Latency' or 'Top Initiator Target LUN Flow Latency' dashboard	
Workaround: Manually select the measures to plot the graph in 'Top Initiator Target Flow Latency' or 'Top Initiator Target LUN Flow Latency' dashboard	
Recovery: Manually select the measures to plot the graph in 'Top Initiator Target Flow Latency' or 'Top Initiator Target LUN Flow Latency' dashboard	

Defect ID: DEFECT000561615	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Dashboards
Symptom: User will be able to find the customized widgets created using "Analytics Monitoring".	
Condition: AMP flag is disabled.	

Defect ID: DEFECT000561679	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Policy Monitor
Symptom: The MAPS configuration dialog will be showing loading MAPS policies message until support save is completed	
Condition: The MAPS configuration is launched when the Technical Support Save data collection in progress	

Defect ID: DEFECT000561863	
Technical Severity: High	Probability: Low
Product: Network Advisor	Technology: Application Management
Reported In Release: Network Advisor 12.4.2	Technology Area: Server Properties
Symptom: Web server and Main server will stop after running for 6 hours after fresh installation	
Condition: Running Network Advisor with more than 2000 VLANs	

Defect ID: DEFECT000561874	
Technical Severity: High	Probability: Medium
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Discovery
Symptom: Network Advisor Server performance has slowed and observed that the DB size increased to 133GB	
Condition: Network Advisor is managing and monitoring the below device for a period of 2 weeks. - Products – 178 - Fabric – 13 - Portcount - 480	
Workaround: Observed only in one case and restarting services resolves the issue	

Defect ID: DEFECT000562125	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Fabric Vision (SAN)
Symptom: In MAPS add/edit/view policy dialog, the categories shows "Analytics Switch"	
Condition: Whenever the MAPS add/edit/view policy dialog are opened for AMP switch which has MAPS enabled	

Defect ID: DEFECT000562181	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Dashboards
Symptom: From Historical graph, user cannot add more flows for monitoring	
Condition: User launched Historical Graph from Dashboard to monitoring a particular flow	
Workaround: Launch the historical/real-time graph by selecting the fabric/switch in Topology will load all the subflows	

Defect ID: DEFECT000562544	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Fabric Vision (SAN)
Symptom: Incorrect error message "No flow available for the selected flow" displayed in Flow Monitor dialog.	
Condition: when filter is enabled and moving flows for monitoring	

Defect ID: DEFECT000562562	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: View Management / Topology
Symptom: User is unable to see the F port connections in topology	
Condition: This issue can occur after firmware upgrade on the switches.	

Defect ID: DEFECT000562652	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Dashboards
Symptom: Sub flow id is shown in Performance Dashboard Monitor Targets dialog and Legend of Analytics Historical and Real Time Graph	
Condition: when creating Time series customized widget	

Defect ID: DEFECT000562655	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Device Management
Reported In Release: Network Advisor 12.4.2	Technology Area: Host
Symptom: Properties dialog for host adapter ports cannot be launched	
Condition: Selecting the Properties icon for the managed host port	
Workaround: Right click on the port and select the adapter port properties.	

Defect ID: DEFECT000562791	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Fabric Vision (SAN)
Symptom: Stats columns shown as inactive in Flow Monitor dialog	
Condition: Active flows are monitored in Flow Monitor dialog	

Defect ID: DEFECT000562800	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Fabric Vision (SAN)
Symptom: Sorting functionality does not work for LUN ID in Flow Monitor dialog	
Condition: When trying to sort the LUN column in Flow Monitor dialog.	

Defect ID: DEFECT000562864	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Device Management
Reported In Release: Network Advisor 12.4.2	Technology Area: Virtual Fabric (SAN)
Symptom: User will see status twice for operations performed during Logical Switches configurations,	
Condition: May occur during any Logical Switches configurations like Create, Update, Delete Logical Switch , etc.	

Defect ID: DEFECT000562918	
Technical Severity: High	Probability: Medium
Product: Network Advisor	Technology: Device Management
Reported In Release: Network Advisor 12.4.2	Technology Area: Virtual Fabric (SAN)
Symptom: Customer is not able to discover or get the recent details from switch.	
Condition: The Ethernet interface of the Windows machine where Network Advisor is installed behaves incorrectly.	
Workaround: Try to restart the Network Advisor server and discover the switch.	
Recovery: Once the Network Advisor server is restarted, the user can see the recent data from the switch and is able to discover the new FOS switch.	

Defect ID: DEFECT000562991	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Fabric Vision (SAN)
Symptom: SCSI label is shown as SCS label, "l" text in the label is hidden.	
Condition: Uncheck the SCSI check box in Flow Monitoring dialog	

Defect ID: DEFECT000563126	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Device Management
Reported In Release: Network Advisor 12.4.2	Technology Area: VLAN
Symptom: VLAN IP Operation failed error is observed when editing the saved deployment after clicking OK button in VLANS Deployments page.	
Condition: When the user tries to edit the saved VLAN configuration and deploy	

Defect ID: DEFECT000563160	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Application Management
Reported In Release: Network Advisor 12.4.2	Technology Area: Active Sessions
Symptom: User will see master log message stating that FOS Support Save operation is aborted, even though the actual operation gets completed successfully. At the end of the Support Save Collection operation, User will also see master log message that Support Save got completed.	
Condition: May occur when Support Save is scheduled for any Fabric OS Director type switches.	
Workaround: Ignore the 'operation aborted' master log message, if the actual Support Save gets completed user will see another message stating that the Support Save is collected successfully.	

Defect ID: DEFECT000563275	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Dashboards
Symptom: Read/Write Pending IOs are displayed as decimal values in Analytic Monitoring dashboard and sometimes it is displayed as zero	
Condition: Analytic flows are monitored in Network Advisor	

Defect ID: DEFECT000563347	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Fabric Vision (SAN)
Symptom: On launching the Violations dialog for a flow from the Flow Vision monitoring dialog, the Time Scope drop down in the Violations dialog lists only one value - '30 mins'. Other time scopes like '6 Hours', '1 Day' etc do not display in the drop down.	
Condition: Launch Violations dialog for a flow from the Flow Vision monitoring dialog.	
Workaround: Launch Violations dialog to view the violations for a specific flow from the Analytics Dashboard..	

Defect ID: DEFECT000563350	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Fabric Vision (SAN)
Symptom: Policy creation/edit/import/distribute on Analytics Monitoring Platform containing rules for measure 'AMP_RX_IOPS' on a non-default switch will fail.	
Condition: Rules for measure 'AMP_RX_IOPS' are present in a policy that is going to be created/edited/imported or distributed on a non default Analytics Monitoring Platform.	

Defect ID: DEFECT000563352	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Fabric Vision (SAN)
Symptom: Violations dialog will display empty values in the 'Category' column for violations from AMP Health category.	
Condition: If violations belonging to the AMP Health category are displayed in the Violations dialog, then the corresponding 'Category' column will not display the category name.	

Defect ID: DEFECT000563372	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Fabric Vision (SAN)
Symptom: Violation column is not rendered with specified color in Flow Monitor dialog.	
Condition: When the count of violation increases for a subflow in Flow Monitor dialog.	

Defect ID: DEFECT000563376	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Dashboards
Symptom: Detailed View dialog is launched with incorrect "Data Size" measure selection for Top Initiator/Target Port widgets	
Condition: Analytic flows are monitored in Network Advisor - Flow Monitor dialog and .Dashboard	

Defect ID: DEFECT000563419	
Technical Severity: High	Probability: Low
Product: Network Advisor	Technology: Device Management
Reported In Release: Network Advisor 12.4.2	Technology Area: Zoning
Symptom: User will not be able to Activate Zone Configuration	
Condition: Applicable only if the Zone Configuration contains TI Zones with failover disabled and if the fabric is a logical fabric and contains base switch or configured to use XISL.	
Workaround: Enable TI Zone failover and try again.	

Defect ID: DEFECT000563485	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Application Management
Reported In Release: Network Advisor 12.4.2	Technology Area: Server Management Console
Symptom: In large environments, in rare scenarios Network Advisor may run out of memory and restart.	
Condition: Extremely large networks with huge number of devices and or a lot of performance data.	
Recovery: Increase the memory allocation using the option in Options dialog.	

Defect ID: DEFECT000563494	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Performance
Reported In Release: Network Advisor 12.4.2	Technology Area: Historical Data
Symptom: Existing subflows are removed in Historical/Real Time Graph when adding new subflows to existing lists.	
Condition: Launching the Performance graphs display only with the last selected flow.	
Workaround: Select the sub-flow from the selected flows table and perform the action.	

Defect ID: DEFECT000563707	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Application Management
Reported In Release: Network Advisor 12.4.2	Technology Area: Installation & Migration
Symptom: Migration will be failed in 32-bit Linux servers.	
Condition: If we migrate from pre 12.4.2 to 12.4.2 in 32-bit Linux servers, migration will be failed.	

Defect ID: DEFECT000563748	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Application Management
Reported In Release: Network Advisor 12.4.2	Technology Area: Login dialog
Symptom: In some cases the remote client for Network Advisor doesn't work in Windows 2012 Datacenter version	
Condition: This issue is seen in Windows 2k12 DC version alone	
Workaround: Use remote client bundle to launch remote client.	

Defect ID: DEFECT000563869	
Technical Severity: High	Probability: Medium
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: View Management / Topology
Symptom: Network Advisor does not display the real time sys_mon_analytics_stats for more than ten minutes.	
Condition: Network Advisor server monitoring an AMP switch that is monitoring RFM flows from a layer 2 fabric that has 12 hosts talking to a target. The hosts generates read/write traffic for size = 514k.	
Recovery: Wait for 10 mins for the stats to recover.	

Defect ID: DEFECT000563978	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Reports
Symptom: Generated PDF report doesn't show complete flow measure details.	
Condition: Generate PDF reports through schedule for templates "Initiator-Target Flow IO Analytics Latency Time Series " and "Initiator-Target Flow IO Analytics Performance Time Series "	
Workaround: Use non-PDF options	

Defect ID: DEFECT000564338	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Application Management
Reported In Release: Network Advisor 12.4.2	Technology Area: Installation & Migration
Symptom: External FTP is selected by default during migration when source is having internal FTP selected.	
Condition: Install pre-12.4.2 Network Advisor with Internal FTP is selected in FTP page in configuration wizard and migrate to 12.4.2 Network Advisor.	
Workaround: Manually select the Internal FTP option in the FTP Page	

Defect ID: DEFECT000564445	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Fabric Vision (SAN)
Symptom: User is not able to edit the groups for the Network OS	
Condition: The Network OS cluster has mix of both MAPS enabled and disabled switches	

Defect ID: DEFECT000564586	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Performance
Reported In Release: Network Advisor 12.4.2	Technology Area: Historical Data
Symptom: Newly added flows overwrites the existing flows in the selection.	
Condition: Launch Flow Vision dialog with existing flows and try to add new flows to the RHS panel.	

Defect ID: DEFECT000564592	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: View Management / Topology
Symptom: If user places the mouse pointer on AMP switch in Topology, Tool Tip dialogue displays Product Type wrongly as switch instead of Analytics Monitoring Platform.	
Condition: When user places the mouse pointer on AMP switch in Topology.	
Workaround: User can get correct product type either in property sheet of device or in product tree.	

Defect ID: DEFECT000564658	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Fabric Vision (SAN)
Symptom: User will not able to get the MAPS configurations for the VDX 8770-4 devices	
Condition: Applicable for all VDX 8770-4 devices from Network Advisor	

Defect ID: DEFECT000565018	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.2	Technology Area: Dashboards
Symptom: "Top Initiator Target LUN flow widget" in Dashboard widget is not displaying the stats	
Condition: Analytic flows are monitored in Network Advisor and in Dashboard select Settings option in the ITL widget and select OK .	

Defects closed with code change in IBM Network Advisor 12.4.2

This section lists the defects with Critical, High and Medium technical severity closed with a code change as of Aug 25, 2015 in IBM Network Advisor 12.4.2.

Defect ID: DEFECT000547663	
Technical Severity: High	Probability: Medium
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.3.3	Technology Area: Reports
Symptom: Cannot launch sflow report in Linux environment.	
Condition: If they are using Xserver to launch Network Advisor and are trying to generate Sflow report.	

Defect ID: DEFECT000553698	
Technical Severity: Medium	Probability: Low
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.3.4	Technology Area: Discovery
Symptom: User is not allowed to enter more than 16 characters in the password fields of IP Discovery dialog when selecting 'SHA' as authentication protocol.	
Condition: User enters more than 16 characters in the password fields of IP Discovery dialog when selecting 'SHA' as authentication protocol.	

Defect ID: DEFECT000554049	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Security
Reported In Release: Network Advisor 12.3.3	Technology Area: Security Vulnerability
Symptom: SSH weak MAV Algorithms are enabled and facing security Vulnerability in customer environment.	
Condition: Run Nessus Scan to get the Security vulnerability	

Defect ID: DEFECT000555981	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Partner Integration
Reported In Release: Network Advisor 12.3.1	Technology Area: SMI Agent
Symptom: Topology details are not received as part of Brocade_TopologyView output for NPIV ports attached with Access Gateway devices	
Condition: Querying enumerate instance for Brocade_TopologyView class	

Defect ID: DEFECT000556814	
Technical Severity: Low	Probability: High
Product: Network Advisor	Technology: Application Management
Reported In Release: Network Advisor 12.3.4	Technology Area: Options dialog
Symptom: Network Advisor still listens to TFTP port ,even though it is set to use secure communications (SCP/SFTP) for file transfer.	
Condition: Network Advisor is set to use secure communications (SCP/SFTP) for file transfer, TFTP is still open	

Defect ID: DEFECT000557611	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.1	Technology Area: Fabric Vision (SAN)
Symptom: MAPS Violation count for flows will always list 0 in Flow Monitoring dialog	
Condition: When MAPS Violations are received from the Analytics Monitoring Platform for the sys_mon_analytics flow	

Defect ID: DEFECT000558171	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.1	Technology Area: Menu & Toolbars
Symptom: Cannot Enable Logical port which is already in Disabled from Device Tree or Topology.	
Condition: Enable the Logical Port from Device tree or Topology	

Defect ID: DEFECT000559314	
Technical Severity: High	Probability: Low
Product: Network Advisor	Technology: Device Management
Reported In Release: Network Advisor 12.4.1	Technology Area: Device configurations
Symptom: The MAPS enable dialog will list already MAPS enabled VDX 6740T-1G devices	
Condition: Applicable for all MAPS enabled VDX 6740T-1G devices	

Defect ID: DEFECT000559968	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.1	Technology Area: Discovery
Symptom: Rigel MOR device is not properly discovered by Network Advisor.	
Condition Discover Rigel MOR device in Network Advisor 12.3.1 release	

Defect ID: DEFECT000559970	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.1	Technology Area: Discovery
Symptom: Rigel MOR device is not properly discovered by Network Advisor.	
Condition Discover Rigel MOR device in Network Advisor 12.3.1 release	

Defect ID: DEFECT000559971	
Technical Severity: Medium	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.1	Technology Area: View Management / Topology
Symptom: VDX 6940-144S is shown with the wrong icon and appears to have flexport capability	
Condition: This is seen when the device is discovered in Network Advisor.	

Defect ID: DEFECT000559972	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.1	Technology Area: Discovery
Symptom: Rigel MOR device is not properly discovered by Network Advisor.	
Condition: Discover Rigel MOR device in Network Advisor 12.3.1 release	

Defect ID: DEFECT000560026	
Technical Severity: Medium	Probability: Medium
Product: Network Advisor	Technology: Device Management
Reported In Release: Network Advisor 12.3.3	Technology Area: Zoning
Symptom: When user tries to activate a zone configuration after adding or removing a zone members from configuration, the zone activation summary shows the devices are unknown	
Condition: this will occur when user tries edit the configuration for the fabric which is not the default selected fabric in the zoning dialog(by changing the zoning scope)	

Defect ID: DEFECT000556814	
Technical Severity: Low	Probability: High
Product: Network Advisor	Technology: Application Management
Reported In Release: Network Advisor 12.3.4	Technology Area: Options dialog
Symptom: Network Advisor still listens to TFTP port ,even though it is set to use secure communications (SCP/SFTP) for file transfer.	
Condition: Network Advisor is set to use secure communications (SCP/SFTP) for file transfer, TFTP is still open	

Defect ID: DEFECT000560042	
Technical Severity: High	Probability: High
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.4.1	Technology Area: Policy Monitor
Symptom: Policy Monitor runs in Professional edition	
Condition: As part of the schedule backup it is executed daily at 8:00 AM	

Defect ID: DEFECT000560800	
Technical Severity: High	Probability: Medium
Product: Network Advisor	Technology: Monitoring
Reported In Release: Network Advisor 12.3.3	Technology Area: Discovery
Symptom: The new Aruba AP devices are not getting discovered in Network Advisor.	
Condition: Discover new Aruba AP devices	